

INDUSTRIAL COMPONENT DATA

500R20 EATON ELECTRIC Fuse-link, LV, 100 A, AC 690V, NH1, gL/gG, IEC, dual indicator, insulated gripping lugs

Brand: EATON - MOELLER | Manufacturer Part Number: 500R20



Manufacturer	EATON - MOELLER
MPN / Reference	500R20
Catalog number	10000
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-6F0D3B7EBF
Generated	2026-08-06

Product Overview

500A 690V AC INDUSTRIAL BS88 FUSE

Fuse-link, low voltage, 500 A, AC 660 V, BS88, 74 x 112 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 500 A, AC 660 V, BS88, 74 x 112 mm, gL/gG, BS, offset bolted tags (slotted), 94 mm fixing centres, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number 500R20 EAN 5027590049542

Product Length/Depth 112 mm Product Height 75 mm Product Width 75 mm Product Weight 932 g Compliances CE

Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 500 A Voltage rating 660 V Voltage type AC Breaking capacity 80 kA Class Class gG/gL Product specifications

Fuse type R20 Construction BS88

ETIM for 500R20 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

660 V

Rated current (EF000227)

500 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

38 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

94 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 500R20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.