

INDUSTRIAL COMPONENT DATA

500AMP 240V AC BS88 FUSE GSA500 EATON ELECTRIC

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 500AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	500AMP 240V AC BS88 FUSE
Catalog number	GSA500
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-97B8C873FF
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS

500AMP 240V AC BS88 FUSE

Fuse-link, high speed, 500 A, AC 240 V, DC 200 V, BS88, 35 x 78 x 85 mm, aR, BS

Fuse, Fuse-link, high speed, 500 A, AC 240 V, DC 200 V, BS88, 35 x 78 x 85 mm, aR, BS, offset bolted tags (dual barrel), Protection of semi-conductor devices, BS88-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series High speed fuses
--------------	---

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number GSA500 EAN 5027590502504

Product Length/Depth 85 mm Product Height 35 mm Product Width 78 mm Product Weight 333 g Compliances CE Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 500 A

Breaking capacity 100 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR

(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 100 kA Rated voltage AC 240 V

Rated voltage DC 200 V Center-to-center distance of connections 60.3 mm Mounting dimension M10 Current type AC/DC

Class Class aR Fuse shape Offset dual barrel bolted tags Color None Construction size Other Voltage rating 240 V Fuse

type GSA Fuse system (according to IEC 60269) Other

ETIM for GSA500 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

240 V

Rated voltage DC (EF012281)

200 V

Rated current (EF000227)

500 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

100 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

60.3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 500AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.