

INDUSTRIAL COMPONENT DATA

500V 500A NH4 FUSE gG 500NHG4G 0001664093 EATON ELECTRIC Fuse-link, LV, 1000 A, AC 500 V, NH4, gL/gG, IEC, S..

Brand: EATON - MOELLER | Manufacturer Part Number: 500V 500A NH4 FUSE gG



Manufacturer	EATON - MOELLER
MPN / Reference	500V 500A NH4 FUSE gG
Catalog number	500NHG4G
Category	Low Voltage HRC fuse
Minimum order	1 Pcs
Document ID	EO-4AE754B550
Generated	2026-08-06

Product Overview

Fuse-link, LV, 1000 A, AC 500 V, NH4, gL/gG, IEC, single indicator, live gripping lugs

fuse cartridge, BT 500 A, AC 500 V, NH4, gL/gG, IEC, single indicator, metal terminals

500V 500A NH4 FUSE gG - Fuse-link, low voltage, 500 A, AC 500 V, 120 kA, NH4, gL/gG, IEC, single indicator, live gripping lugs

Fuse, Fuse-link, low voltage, 500 A, AC 500 V, NH4, gL/gG, IEC, single (top) indicator system, square-body with slotted blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

EL-Nummer (Norway)1664090Fuse-link, low voltage, 500 A, AC 500 V, 120 kA, NH4, gL/gG, IEC, single indicator, live gripping lugsFuse, Fuse-link, low voltage, 500 A, AC 500 V, NH4, gL/gG, IEC, single (top) indicator system, square-body with slotted blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kADelivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]500 ARated voltageAC 500 VConstruction sizeNH4Utilization categorygL/gGStatus indicatorsingle indicatorDescriptionlive gripping lugsBreaking Capacity120 kAStandard/ApprovalIECShapesquare body with slotted blade contactsStandards/RegulationsIEC 60269-2 fuse system A

DIN 43620

VDE 0636-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size NH4 Rated current 500 A Rated voltage 500 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 500NHG4G Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH4

Voltage type (EF000187)

AC

Rated current (EF000227)

500 A

Rated voltage AC (EF0076...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 500V 500A NH4 FUSE gG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.