

INDUSTRIAL COMPONENT DATA

500V 50AMP SEMI-COND.FUSE FWH-50BI EATON ELECTRIC

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 500V 50AMP SEMI-COND.FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	500V 50AMP SEMI-COND.FUSE
Catalog number	FWH50BI
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-9430B4116F
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS

Fuse, Fuse-link, high speed, 50 A, AC 500 V, DC 500 V, 21 x 81 mm, aR, UL, with indicator, cylindrical, centre-bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann fuses
--------------	----------------------------------

Additional Product Information

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS Fuse, Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS, offset bolted tags (slotted), Special 80 mm fixing centres, thyristor fuse, traction, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories BH-0111 fuse holder [Delivery program Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 50 A Rated voltage AC 690 V DC 500 V Construction size BS88 Size 18 x 96 mm Utilization category aR Description Special 80 mm fixing centres thyristor fuse Breaking Capacity 200 kA usable for size/applications traction Standard/Approval BS Shape offset bolted tags (slotted) Standards/Regulations BS88-4

IEC 60269-4 Optional accessories BH-0111 fuse holder , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 50 A Rated voltage 690 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]

ETIM for FWH-50BI Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated current (EF000227)

50 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 500V 50AMP SEMI-COND.FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.