

INDUSTRIAL COMPONENT DATA

50A 500V DC BS88 PT1 FUSE 50KS07 EATON ELECTRIC

Fuse-link, LV, 315 A, AC 415 V, BS88/B3, BS88/B4, 38 x 136 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 50A 500V DC BS88 PT1 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	50A 500V DC BS88 PT1 FUSE
Catalog number	50KS07
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-0A58FDB2E9
Generated	2026-08-06

Product Overview

Fuse-link, LV, 315 A, AC 415 V, BS88/B3, BS88/B4, 38 x 136 mm, gL/gG, BS

50A 500V DC BS88 PT1 FUSE

Fuse-link, low voltage, 50 A, DC 500 V, BS88/A3, 27 x 91 mm, BS

Fuse, Fuse-link, low voltage, 50 A, DC 500 V, BS88/A3, 27 x 91 mm, gL/gG, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number 50KS07 EAN 5027590482998

Product Length/Depth 86 mm Product Height 36 mm Product Width 36 mm Product Weight 80.3 g Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 50 A Voltage rating 500 V Voltage type DC Breaking capacity 40 kA Class Class gG/gL Product

specifications

Fuse type KS07 Construction BS88/A3

ETIM for 50KS07 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A3

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

500 V

Rated current (EF000227)

50 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

40 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

71.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 50A 500V DC BS88 PT1 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.