

INDUSTRIAL COMPONENT DATA

XL70F50 EATON ELECTRIC Fuse-link, high speed, 50 A, AC 700 V, DC 700 V, 22 x 115 mm, aR, UL

Brand: EATON - MOELLER | Manufacturer Part Number: XL70F50



Manufacturer	EATON - MOELLER
MPN / Reference	XL70F50
Catalog number	XL70F50
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-9944864964
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 700 V, DC 700 V, 22 x 115 mm, aR, UL

High speed North American fuse, 700V, 50A, 200 kAIC, Non indicating, bolted tags, UL248-13, class aR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 50 A, AC 700 V, DC 700 V, 22 x 115 mm, aR, ULFuse, Fuse-link, high speed, 50 A, AC 700 V, DC

700 V, 22 x 115 mm, aR, UL, centre-bolted tags, UL 248-13, Breaking Capacity 200 kADelivery program

Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]50 ARated voltageAC 700 V

DC 700 VSize22 x 115 mmUtilization categoryaRBreaking Capacity200 kAStandard/ApprovalULShapecentre-bolted

tagsStandards/RegulationsUL 248-13Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current50 ARated voltage700 VVoltage typeACRated switching capacity200

kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping

lugs (IMGL)No

ETIM for XL70F50 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

700 V

Rated current (EF000227)

50 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XL70F50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.