

INDUSTRIAL COMPONENT DATA

NH FUSE 50A 690V gG SIZE 00 50NHG00B-690 EATON

ELECTRIC Fuse-link, LV, 100 A, AC 690 V, NH00, gL/gG, IEC, du..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 50A 690V gG SIZE 00



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 50A 690V gG SIZE 00
Catalog number	50NHG00B-690
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-174AA6C67C
Generated	2026-08-06

Product Overview

Fuse-link, LV, 100 A, AC 690 V, NH00, gL/gG, IEC, dual indicator, live gripping lugs

NH FUSE 50AMP 690V gG SIZE 00

NH FUSE 50AMP 690V gG SIZE 00 - Fuse-link, low voltage, 50 A, AC 690 V, 120 kA, NH00, gL/gG, IEC, dual indicator, live gripping lugs

Fuse, fuse-link, low voltage, 50 A, AC 690 V, NH00, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

EL-Nummer (Norway)0001664107Fuse-link, low voltage, 50 A, AC 690 V, 120 kA, NH00, gL/gG, IEC, dual indicator, live gripping lugsFuse, fuse-link, low voltage, 50 A, AC 690 V, NH00, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kADelivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]50 ARated voltageAC 690 VConstruction sizeNH00Utilization categorygL/gGStatus indicatordual indicatorDescriptionlive gripping lugsBreaking Capacity120 kAusable for size/applicationsindustrialStandard/ApprovalIECShapesquare body with knife blade contactsStandards/RegulationsIEC 60269-2 fuse system A

DIN 43620

VDE 0636-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size NH00 Rated current 50 A Rated voltage 690 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 50NHG00B-690 Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH00

Voltage type (EF000187)

AC

Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 50A 690V gG SIZE 00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.