

INDUSTRIAL COMPONENT DATA

NH FUSE 50AMP 690V gG SIZE 0 50NHG0B-690 NH FUSE 50AMP 690V gG SIZE 0 DUAL IND EATON ELECTRIC Fuse-link, LV,..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 50AMP 690V gG SIZE 0



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 50AMP 690V gG SIZE 0
Catalog number	NH FUSE 50AMP 690V gG SIZE 0 DUAL IND
Category	Low Voltage HRC fuse
Minimum order	1 Pcs
Document ID	EO-DFE2B1FE3A
Generated	2026-08-06

Product Overview

Fuse-link, LV, 100 A, AC 690V, NH1, gL/gG, IEC, dual indicator, insulated gripping lugs

NH FUSE 50AMP 690V gG SIZE 0

NH FUSE 50AMP 690V gG SIZE 0 - Fuse-link, LV, 50 A, AC 690 V, NH0, gL/gG, IEC, dual indicator, live gripping lugs

Fuse, Fuse-link, low voltage, 50 A, AC 690 V, NH0, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, LV, 50 A, AC 690 V, NH0, gL/gG, IEC, dual indicator, live gripping lugs
Fuse, Fuse-link, low voltage, 50 A, AC 690 V, NH0, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA
Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
50 A
Rated voltage
AC 690 V
Construction size
NH0
Utilization category
gL/gG
Status indicator
dual (combination) indicator system
Description
live gripping lugs
Breaking Capacity
120 kA
Standard/Approval
IEC
Shapes
square body with knife blade contacts
Standards/Regulations
IEC 60269-2 fuse system A

DIN 43620

VDE 0636-2
Technical data
ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size NH0 Rated current 50 A Rated voltage 690 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 50NHG0B-690 Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH0

Voltage type (EF000187)

AC

Rated current (EF000227)

50 A

Rated voltage AC (EF007682)

690 V

Rated s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 50AMP 690V gG SIZE 0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.