

INDUSTRIAL COMPONENT DATA

550A TYPE T FUSE (1) 550CFMM EATON ELECTRIC Microswitch, high speed, 2 A, AC 250 V, Switch T1, IEC

Brand: EATON - MOELLER | Manufacturer Part Number: 550A TYPE T FUSE (1)



Manufacturer	EATON - MOELLER
MPN / Reference	550A TYPE T FUSE (1)
Catalog number	550CFMM
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-94AD861495
Generated	2026-08-05

Product Overview

Microswitch, high speed, 2 A, AC 250 V, Switch T1, IEC

550A 690V TYPE T FUSE (1)

Fuse, Fuse-link, high speed, 550 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS, centre-bolted tags (dual barrel), 110 mm fixing centres, dual-barrel, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 550 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS Fuse, Fuse-link, high speed, 550 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS, centre-bolted tags (dual barrel), 110 mm fixing centres, dual-barrel, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 550 A Rated voltage AC 690 V DC 450 V Construction size BS88 Size 83 x 136 mm Utilization category aR Description 110 mm fixing centres dual-barrel Breaking Capacity 200 kA usable for size/applications protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters Standard/Approval BS Shape centre-bolted tags (dual barrel) Standards/Regulations BS88-4

IEC 60269-4 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015]) Construction size Other Rated current 550 A Rated voltage 690 V Voltage type AC/DC Rated switching
capacity 200 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator None
Insulated metal gripping lugs (IMGL) No]

ETIM for 550CFMM Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 550A TYPE T FUSE (1) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.