

INDUSTRIAL COMPONENT DATA

560A 690V AC TYPE T FUSE 560MMT EATON ELECTRIC

Fuse-link, high speed, 400 A, AC 690 V, DIN 00, 30 x 51 x 100..

Brand: EATON - MOELLER | Manufacturer Part Number: 560A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	560A 690V AC TYPE T FUSE
Catalog number	560MMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-BD67434A89
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 690 V, DIN 00, 30 x 51 x 100 mm, aR, DIN, IEC, type T indicator

560A 690V AC TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Double barrel, 560A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

Fuse, Fuse-link, high speed, 560 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS, centre-bolted tags (dual barrel), DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-3133

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 560MMT EAN 5027590049832

UPC 051712835732 Product Length/Depth 98 mm Product Height 40 mm Product Width 97 mm Product Weight 478 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4

UL recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 560 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V
Rated voltage DC 350 V Center-to-center distance of connections 85 mm Mounting dimension M8 Current type AC/DC
Class Class aR Clearing (I₂T) 430000 Watt losses 64 W Fuse shape Center dual barrel bolted tags Pre arc (I₂T) 60000
Color None Interrupt rating 200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC) Connection Blade end x blade end
Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type
MMT Suitable for MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 560MMT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 560A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.