

INDUSTRIAL COMPONENT DATA

5A TIME DELAY FUSES TXU1250 EATON ELECTRIC

Fuse-link, LV, 1250 A, AC 660 V, DC 300 V, BS88/D1, 102 x 200 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: 5A TIME DELAY FUSES



Manufacturer	EATON - MOELLER
MPN / Reference	5A TIME DELAY FUSES
Catalog number	TXU1250
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-F2428725DF
Generated	2026-08-06

Product Overview

Fuse-link, LV, 1250 A, AC 660 V, DC 300 V, BS88/D1, 102 x 200 mm, gG

1250A BS88 660V AC 300V DC FUSES

1250A BS88 660V AC 300V DC FUSES - Fuse-link, low voltage, 1250 A, AC 660 V, BS88/D1, 102 x 200 mm, gL/gG, BS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 1250 A, AC 660 V, BS88/D1, 102 x 200 mm, gL/gG, BSFuse, Fuse-link, LV, 1250 A, AC 660 V, DC 300 V, BS88/D1, 102 x 200 mm, gG, BS, centre-bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

Delivery program
Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]_n1250 ARated voltageAC 660 VConstruction sizeBS88/D1Size102 x 200 mmUtilization categorygL/gGStandard/ApprovalBSShapecylindrical with centre-bolted tagsStandards/RegulationsBS88 IEC 60269

EACTechnical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015])Construction sizeOtherRated current1250 ARated voltage660 VVoltage typeAC/DCRated switching

capacity80 kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorNoneInsulated
metal gripping lugs (IMGL)No
ETIM for TXU1250 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
660 V
Rated voltage DC (EF012281)
300 V
Rated current (EF000227)
1250 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 5A TIME DELAY FUSES with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.