

INDUSTRIAL COMPONENT DATA

60AMP 750V TRACTION FUSE FWK-60A25F EATON

ELECTRIC Fuse-link, high speed, 10 A, AC 750 V, DC 750 V, 20 x 127..

Brand: EATON - MOELLER | Manufacturer Part Number: 60AMP 750V TRACTION FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	60AMP 750V TRACTION FUSE
Catalog number	FWK60A25F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-A2D455DAED
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 10 A, AC 750 V, DC 750 V, 20 x 127 mm, aR, IEC

Fuse, Fuse-link, high speed, 60 A, AC 750 V, DC 750 V, 25 x 146 mm, aR, IEC, cylindrical, traction, IEC 60269, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann fuses
--------------	----------------------------------

Additional Product Information

Fuse-link, high Speed, 60 A, DC 750 V, 28 x 138 mm, gL/gG, IEC Fuse, Fuse-link, High Speed, 60 A, DC 750 V, 28 x 138 mm, gL/gG, IEC, offset bolted tags (slotted), traction, IEC 60269, Breaking Capacity 50 kA [Delivery program
Product range Fuse Basic function Fuse-link Field of application High Speed Rated current [I] 60 A Rated voltage DC 750 V
Size 28 x 138 mm Utilization category gL/gG Breaking Capacity 50 kA usable for size/applications traction
Standard/Approval IEC Shape offset bolted tags (slotted) Standards/Regulations IEC 60269 , Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015]) Construction size Other Rated current 60 A Rated voltage 750 V Voltage type DC Voltage type DC Rated switching capacity 50 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]
ETIM for FWK-60A25F Circuit breakers and fuses (EC002704)

Feature Name
Feature Value
Model (EF000010)
Ceramic fuse
Size (EF000088)
Other
Voltage type (EF000187)
DC
Rated current (EF000227)
60 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Type of fuse status indicator (EF004473)
Other
Release characteristic (EF000889)
Other
Power loss at rated current (EF0123...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 60AMP 750V TRACTION FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.