

INDUSTRIAL COMPONENT DATA

63A 500V DC BS88 PT1 FUSE 63KS07 EATON ELECTRIC cartridge fuse, BT, 63 A, DC 500 V, BS88/A3, 26 x 86 mm, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 63A 500V DC BS88 PT1 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	63A 500V DC BS88 PT1 FUSE
Catalog number	63KS07
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-429B171D2D
Generated	2026-08-06

Product Overview

cartridge fuse, BT, 63 A, DC 500 V, BS88/A3, 26 x 86 mm, BS

63A 500V DC BS88 PT1 FUSE

Fuse-link, low voltage, 63 A, DC 500 V, BS88/A3, 26 x 86 mm, BS

Fuse, Fuse-link, low voltage, 63 A, DC 500 V, BS88/A3, 26 x 86 mm, BS, offset bolted tags, Breaking Capacity 40 kA, Ceramic body, Optional accessories fuse-holder CM63F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number 63KS07 EAN 5027590485180

Product Length/Depth 86 mm Product Height 27 mm Product Width 27 mm Product Weight 81 g Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 63 A Voltage rating 500 V Voltage type DC Breaking capacity 40 kA Class Class gG/gL Product specifications

Fuse type KS07 Construction BS88/A3

ETIM for 63KS07 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A3

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

500 V

Rated current (EF000227)

63 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

40 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

71.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 63A 500V DC BS88 PT1 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.