

INDUSTRIAL COMPONENT DATA

63AMP 240V AC BS88 FUSE 63LET EATON ELECTRIC

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 63AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	63AMP 240V AC BS88 FUSE
Catalog number	63LET
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-B8E158DD16
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

63AMP 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 63A, 280 VAC/150 VDC (UL), Class aR, 200 kA RMS Sym., Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

Fuse, Fuse-link, high speed, 63 A, AC 240 V, DC 150 V, BS88, 18 x 56 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 63LET EAN 5027590485197 UPC 051712836517 Product Length/Depth 55 mm Product Height 18 mm Product Width 18 mm Product Weight 32 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4 Electrical data

Amperage Rating 63 A Voltage rating 280 V Rated voltage AC 280 V Rated voltage DC 150 V Interrupt rating 200 kA RMS Sym, 50 kA DC at 150 Vdc Class Class aR Pre arc (I2T) 180 Clearing (I2T) 2200 Watt losses 9 W Product specifications Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None Compatible Trip indicator/Microswitch

Suitable for TI500 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

ETIM for 63LET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

280 V

Rated voltage DC (EF012281)

150 V

Rated current (EF000227)

63 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

9 W

Mounting holes (EF021553)

M6

Centre-to-centre distance of connections (EF021151)

41 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 63AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.