

INDUSTRIAL COMPONENT DATA

NH FUSE 63A 400V GG/GL SIZE 000 63NHG000B-400 BUSSMANN 63A 400V GG 000 63NHG000B-400 EATON ELECTRIC Fuse-link..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 63A 400V GG/GL SIZE 000



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 63A 400V GG/GL SIZE 000
Catalog number	BUSSMANN 63A 400V GG 000 63NHG000B-400
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-AA3D4753A0
Generated	2026-08-06

Product Overview

Fuse-link, LV, 10 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

NH FUSE 63A 400V GG/GL SIZE 000

NH FUSE 63A 400V GG/GL SIZE 000 - Fuse-link, low voltage, 63 A, AC 400 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs

Fuse, fuse-link, low voltage, 63 A, AC 400 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 63 A, AC 400 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs
Fuse, fuse-link, low voltage, 63 A, AC 400 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA
Delivery program
Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I]_n 63 A Rated voltage AC 400 V Construction size NH000 Utilization category gL/gG Status indicator dual indicator Description live gripping lugs Breaking Capacity 120 kA Usable for size/applications industrial Standard/Approval IEC Shapes square body with knife blade contacts Standards/Regulations IEC 60269-2 fuse system A
DIN 43620

VDE 0636-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size NH000 Rated current 63 A Rated voltage 400 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) No

ETIM for 63NHG000B-400 Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH000

Voltage type (EF000187)

AC

Rated current (EF000227)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 63A 400V GG/GL SIZE 000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.