

INDUSTRIAL COMPONENT DATA

6AMP 240V AC BS88 FUSE 6LCT EATON ELECTRIC Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, ..

Brand: EATON - MOELLER | Manufacturer Part Number: 6AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	6AMP 240V AC BS88 FUSE
Catalog number	6LCT
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-1C9DB98ED5
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS

6AMP 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 6A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

Fuse, Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 6LCT EAN 5027590486309 UPC 051712837149 Product Length/Depth 52 mm Product Height 20 mm Product Width 84 mm Product Weight 5.7 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

UL recognized

IEC 60269-4

CCC Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 6 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 240 V
Rated voltage DC 150 V Center-to-center distance of connections 37.4 mm Mounting dimension M6 Current type AC/DC
Class Class aR Clearing (I2T) 9 Watt losses 1 W Fuse shape Offset bolted tags Pre arc (I2T) 2 Color None Interrupt rating
200 kA RMS Sym, 50 kA DC at 150 Vdc Connection Blade end x blade end Construction size Other Mounting method Stud
Packaging type Standard Voltage rating 240 Vac, 150 Vdc Fuse type LCT Suitable for TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 6LCT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 6AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.