

INDUSTRIAL COMPONENT DATA

6AMP 550V AC BS88 gG FUSE NIT6 EATON ELECTRIC

Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 6AMP 550V AC BS88 gG FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	6AMP 550V AC BS88 gG FUSE
Catalog number	NIT6
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-6D9058C757
Generated	2026-08-06

Product Overview

Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

6AMP 550V AC BS88 gG FUSE

6AMP 550V AC BS88 gG FUSE - Fuse-link, low voltage, 6 A, AC 550 V, DC 250 V, 80 kA, BS88/A1, 14 x 56 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 6 A, AC 550 V, DC 250 V, BS88/A1, 14 x 56 mm, gL/gG, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 6 A, AC 550 V, DC 250 V, 80 kA, BS88/A1, 14 x 56 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 6 A, AC 550 V, DC 250 V, BS88/A1, 14 x 56 mm, gL/gG, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20 Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I]_n 6 A Rated voltage AC 550 V

DC 250 V Construction size BS88/A1 Size 14 x 56 mm Utilization category gL/gG Breaking Capacity 80 kA Suitable for

size/applications general industrial applications Standard/Approval BS Shape offset bolted tags

(slotted) Standards/Regulations BS88-2

IEC 60269-2 Optional accessories fuse-holder CM32FC and RS20 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current6 ARated voltage550 VVoltage typeAC/DCRated switching capacity80
kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorNoneInsulated metal
gripping lugs (IMGL)No
ETIM for NIT6 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
A1
Type of current (EF000143)
AC/DC
Rated voltage A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 6AMP 550V AC BS88 gG FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.