

INDUSTRIAL COMPONENT DATA

6AMP 600V AC FERRULE 10 X 38MM FWC-6A10F EATON ELECTRIC Emergency-stop pushbutton, D 38mm, key unlocking, cl..

Brand: EATON - MOELLER | Manufacturer Part Number: 6AMP 600V AC FERRULE 10 X 38MM



Manufacturer	EATON - MOELLER
MPN / Reference	6AMP 600V AC FERRULE 10 X 38MM
Catalog number	FWC-6A10F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-0B0C0BA380
Generated	2026-08-06

Product Overview

Emergency-stop pushbutton, D=38mm, key unlocking, closure according to data

6AMP 600V AC FERRULE 10 X 38MM

Eaton Bussmann series FWC high speed cylindrical fuse, 500 Vac/dc (35-800A only), 6A, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

Fuse, Fuse-link, high speed, 6 A, AC 600 V, 10 x 38 mm, aR, UL, cylindrical, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder CHM1DU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWC-6A10F EAN 5027590499415

UPC 051712796415 Product Length/Depth 38 mm Product Height 11 mm Product Width 11 mm Product Weight 9 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

CSA Certified Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage

Rating 6 A Accessories Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 10 x 38 mm Class Class aR Clearing (I2T) 30 Watt losses 1.5 W Fuse shape Cylindrical Pre arc (I2T) 4 Interrupt rating 200 kAIC Vac Connection Ferrule end x ferrule end Construction size 10 x 38 mm Material Ceramic Packaging type Standard Voltage rating 600 V Fuse type FWC-A10F ETIM for FWC-6A10F Circuit breakers and fuses (EC002704)

Feature Name
Feature Value
Model (EF000010)
Ceramic fuse
Size (EF000088)
10x38 mm
Voltage type (EF000187)
AC/DC
Rated current (EF000227)
6 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Type of fuse status indicator (EF004473)
Other
Release characteristic (EF000889)
Other
Power loss at rated current (EF012389)
1.5 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 6AMP 600V AC FERRULE 10 X 38MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.