

INDUSTRIAL COMPONENT DATA

7.2KV 20Amp 2" DIN Sealed Fuse 7.2TDLSJ20 7-2TDLSJ20 EATON ELECTRIC Fuse-link, medium voltage, 20 A, AC 7.2 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 20Amp 2" DIN Sealed Fuse



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 20Amp 2" DIN Sealed Fuse
Catalog number	7-2TDLSJ20
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-E49B0AC949
Generated	2026-08-06

Product Overview

Fuse-link, medium voltage, 20 A, AC 7.2 kV, 2", 51 x 292 mm, back-up, DIN, with striker

7.2KV 20Amp 2" DIN Sealed Fuse

7.2KV 20Amp 2" DIN Sealed Fuse - Fuse-link, medium voltage, 20 A, AC 7.2 kV, 40 kA, 2", 51 x 292 mm, back-up, DIN, with striker

Fuse, Fuse-link, medium voltage, 20 A, AC 7.2 kV, 2z, 51 x 292 mm, Back-up, DIN, with striker, transformer protection, indoor or outdoor use, DIN 43625, VDE 0670 Part 4, VDE 0670 Part 402, IEC 60282-1, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Fuse-link, medium voltage, 20 A, AC 7.2 kV, 40 kA, 2", 51 x 292 mm, back-up, DIN, with striker
Fuse, Fuse-link, medium voltage, 20 A, AC 7.2 kV, 2", 51 x 292 mm, Back-up, DIN, with striker, transformer protection, indoor or outdoor use, DIN 43625, VDE 0670 Part 4, VDE 0670 Part 402, IEC 60282-1, Breaking Capacity 40 kA
Delivery program

Product range
FuseBasic function
Fuse-linkField of applicationmedium voltage
Rated current [I]_n20 A
Rated voltageAC 7.2 kV
Construction size2"
Size51 x 292 mm
Utilization categoryback-up
Status indicatorwith striker
Breaking Capacity40 kA
Usable for size/applicationtransformer protection

indoor or outdoor use
Standard/ApprovalDINStandards/RegulationsDIN 43625

VDE 0670-4

VDE 0670-402

IEC 60282-1
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 20 A Rated voltage 7.2 kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 40 kA Utilization category Other Application Primary side transformer protection Length 292 mm Diameter 51 mm Performance category according to IEC 60282-1 Back-up With striker Yes Standard DIN Release characteristic Other Installation technique Air
ETIM for 7.2TDL SJ20 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

20 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

40 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Primary side transformer pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 20Amp 2" DIN Sealed Fuse with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.