

INDUSTRIAL COMPONENT DATA

7.2WFNHA25 7.2KV 25AMP 3" MOTORSTART DCR 2474

EATON ELECTRIC Motor fuse-link, medium voltage, 25 A, AC 7.2 k..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2WFNHA25



Manufacturer	EATON - MOELLER
MPN / Reference	7.2WFNHA25
Catalog number	7.2KV 25AMP 3" MOTORSTART DCR 2474
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-9BF4F7220D
Generated	2026-08-06

Product Overview

Motor fuse-link, medium voltage, 25 A, AC 7.2 kV, 76 x 403 mm, back-up, BS, with striker, no tags

7.2KV 25AMP 3" MOTORSTART DCR 2474

7.2KV 25A 3" MOTOR START FUSE - Motor fuse-link, medium voltage, 25 A, AC 7.2 kV, 76 x 403 mm, back-up, BS, with striker, no tags

Fuse, Motor fuse-link, medium voltage, 25 A, AC 7.2 kV, 76 x 403 mm, back-up, BS, with striker, cylindrical, motor protection, BS2692-1, IEC 60282-1, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 25 A, AC 7.2 kV, 76 x 403 mm, back-up, BS, with striker, no tags
Fuse, Motor fuse-link, medium voltage, 25 A, AC 7.2 kV, 76 x 403 mm, back-up, BS, with striker, cylindrical, motor protection, BS2692-1, IEC 60282-1, Breaking Capacity 40 kA
Delivery program

Product range Fuse
Basic function Motor fuse-link
Field of application medium voltage
Rated current [I]_N 25 A
Rated voltage AC 7.2 kV
Size 76 x 403 mm
Utilization category back-up
Status indicator with striker
Breaking Capacity 40 kA
Usable for size/applications motor protection
Standard/Approval BS
Shape cylindrical
Standards/Regulations BS2692-1
IEC 60282-1
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)
Rated current 25 A
Rated voltage 7.2

kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 40 kA Utilization category Other Application Motor protection Length 530 mm Diameter 76 mm Performance category according to IEC 60282-1 Back-up With striker Yes Standard British Standard Release characteristic Other Installation technique Air ETIM for 7.2WFNHA25 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

25 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.04 kA

Utilization category according to IEC 60269 (EF002572)

Other

Length (EF001438)

530 mm

Performance category according to IEC 60282-1 (EF012539)

Back-up

With striker (EF008175)

Yes

Standard (EF009322)

British Standard...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2WFNHA25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.