

INDUSTRIAL COMPONENT DATA

700AMP 700V AC SEMI-COND FUSE FWP-700A EATON ELECTRIC cartridge fuse, ultra rapid, 700, AC 700 V DC 700 V, 5..

Brand: EATON - MOELLER | Manufacturer Part Number: 700AMP 700V AC SEMI-COND FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	700AMP 700V AC SEMI-COND FUSE
Catalog number	FWP-700A
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-0DBCC308F2
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 700, AC 700 V DC 700 V, 51 x 169 mm, UL

700AMP 700V AC SEMI-COND FUSE

Eaton Bussmann series FWP high speed fuse, 250 Vac/dc, 700A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud

Fuse, Fuse-link, high speed, 700 A, AC 700 V, DC 700 V, 51 x 169 mm, UL, cylindrical with centre-bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWP-700A EAN 5027590021838 UPC 051712796057 Product Length/Depth 56 mm Product Height 53 mm Product Width 180 mm Product Weight 588 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

CSA Certified Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage Rating 6 A Breaking capacity 200 kA Fuse indicator Non Indicating Insulated metal gripping lugs (IMGL) No Utilization

category aR (accompanied semiconductor protection) Voltage type AC Rated switching capacity 200 A Rated voltage AC 700 V Rated voltage DC 700 V Mounting dimension Other Center-to-center distance of connections 134.95 mm Current type AC/DC Class Class aR Clearing (I₂T) 300000 at 700 V Watt losses 122 W Fuse shape Cylindrical, center bolted tags Pre arc (I₂T) 54000 Color None Interrupt rating 50 kAIC at 700 Vdc

200 kAIC Vac

200 kAIC Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 700 Vac, 700 Vdc (UL) Fuse type FWP-A Fuse system (according to IEC 60269) Other ETIM for FWP-700A Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

700 V

Rated voltage DC (EF012281)

700 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 700AMP 700V AC SEMI-COND FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.