

INDUSTRIAL COMPONENT DATA

71A 690V AC TYPE T FUSE 71FE EATON ELECTRIC Fuse link, ultra fast, 71 A, AC 690 V, DC 500 V, BS88, 19 x 77 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 71A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	71A 690V AC TYPE T FUSE
Catalog number	71FE
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-DBECDFBACF
Generated	2026-08-06

Product Overview

Fuse link, ultra fast, 71 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS

71A 690V AC TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Single barrel, 71A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 71 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 71FE EAN 5027590488976 UPC 051712837217 Product Length/Depth 82 mm Product Height 39 mm Product Width 91 mm Product Weight 40.5 g

Compliances CE Marked

RoHS Compliant Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 71 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 500 V Center-to-center distance of connections 61.8 mm Mounting dimension M6 Current type AC/DC

Class Class aR Clearing (I2T) 600 at 415 V, 950 at 660 V Watt losses 17 W Fuse shape Offset bolted tags Pre arc (I2T) 210 Color None Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type FE Suitable for EC-600 Trip indicator kit (indicator + clips)
TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 71FE Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 71A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.