

INDUSTRIAL COMPONENT DATA

7.2KV 100AMP 2.5" OIL FUSE 7.2OHGMA100 NZM2-4-XKV2POU-K EATON ELECTRIC cartridge fuse Oil, MT, 100 A, AC 7.2..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 100AMP 2.5" OIL FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 100AMP 2.5" OIL FUSE
Catalog number	NZM2-4-XKV2POU-K
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-E05780365E
Generated	2026-08-06

Product Overview

cartridge fuse Oil, MT, 100 A, AC 7.2 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker
7.2KV 100AMP 2.5" OIL FUSE

7.2KV 100AMP 2.5" OIL FUSE - Oil fuse-link, medium voltage, 100 A, AC 7.2 kV, 40 kA, BS2692 F02, 359 x 63.5 mm,
back-up, BS, IEC, ESI, with striker, oil-tight

Fuse, Oil fuse-link, medium voltage, 100 A, AC 7.2 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker,
cylindrical, oil-tight, protection of primary side transformer, and oil-filled fuse switch combination unit, BS2692-1, IEC
60282-1, ESI 12-8, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Oil fuse-link, medium voltage, 100 A, AC 7.2 kV, 40 kA, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker,
oil-tightFuse, Oil fuse-link, medium voltage, 100 A, AC 7.2 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with
striker, cylindrical, oil-tight, protection of primary side transformer, and oil-filled fuse switch combination unit, BS2692-1, IEC
60282-1, ESI 12-8, Breaking Capacity 40 kADelivery program

Product rangeFuseBasic functionOil fuse-linkField of applicationmedium voltageRated current [I]_n100 ARated voltageAC 7.2
kVConstruction sizeBS2692 F02Size359 x 63.5 mmUtilization categoryback-upStatus indicatorwith
strikerDescriptionoil-tightBreaking Capacity40 kAusable for size/applicationsprotection of primary side transformer, and

oil-filled fuse switch combination unitStandard/ApprovalBS

IEC

ESIShapecylindricalStandards/RegulationsBS2692-1

IEC 60282-1

ESI 12-8Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)Rated current100 ARated voltage7.2 kVVoltage typeACRated frequency50 - 50 HzBreaking capacity40 kAUtilization categoryOtherApplicationPrimary side transformer protectionLength359 mmDiameter63.5 mmPerformance category according to IEC 60282-1Back-upWith strikerYesStandardBritish StandardRelease characteristicOtherInstallation techniqueOil

ETIM for 7.2OHGMA100 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

100 A

Rated voltage (EF000228)

7.2 kV

Voltage type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 100AMP 2.5" OIL FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.