

INDUSTRIAL COMPONENT DATA

7.2KV 125amps"MOTOR START FUSE 7.2WFMSJ125 7-2WFMSJ125 EATON ELECTRIC Auxiliary winding switch, Contacts: 8..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 125amps"MOTOR START FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 125amps"MOTOR START FUSE
Catalog number	7-2WFMSJ125
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-649C8D22A2
Generated	2026-08-06

Product Overview

Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

7.2KV 125amps"MOTOR START FUSE

7.2KV 125amps"MOTOR START FUSE - Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, 63 kA, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker

Fuse, Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, DIN 43625 3z, 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, 63 kA, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker
Fuse, Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA
Delivery program

Product range Fuse Basic function Motor fuse-link Field of application medium voltage Rated current [I] 125 A Rated voltage AC 7.2 kV Construction size DIN 43625 3" Size 76 x 442 mm Utilization category back-up Status indicator with striker Breaking Capacity 63 kA Usable for size/applications motor protection Standard/Approval DIN Shape cylindrical Standards/Regulations DIN 43625

VDE 0670-4

IEC 60282-1 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 25 A Rated voltage 7.2

kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 63 kA Utilization category Other Application Motor

protection Length 530 mm Diameter 76 mm Performance category according to IEC 60282-1 Back-up With

striker Yes Standard DIN Release characteristic Other Installation technique Air

ETIM for 7.2WFM SJ125 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

25 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.063 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Motor protection

Length (EF001438)

442 mm

Diameter (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 125amps "MOTOR START FUSE" with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.