

INDUSTRIAL COMPONENT DATA

7.2KV 125amps"MOTOR START FUSE 7.2WFMSJ125 7-2WFMSJ125 EATON ELECTRIC Auxiliary winding switch, Contacts: 8..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 125amps"MOTOR START FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 125amps"MOTOR START FUSE
Catalog number	7-2WFMSJ125
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-649C8D22A2
Generated	2026-08-06

Product Overview

Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

7.2KV 125amps"MOTOR START FUSE

7.2KV 125amps"MOTOR START FUSE - Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, 63 kA, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker

Fuse, Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, DIN 43625 3z, 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, 63 kA, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker
Fuse, Motor fuse-link, medium voltage, 125 A, AC 7.2 kV, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA
Delivery program

Product rangeFuseBasic functionMotor fuse-linkField of applicationmedium voltageRated current [I]125 ARated voltageAC 7.2 kVConstruction sizeDIN 43625 3"Size76 x 442 mmUtilization categoryback-upStatus indicatorwith strikerBreaking Capacity63 kAusable for size/applicationsmotor protectionStandard/ApprovalDINShapecylindricalStandards/RegulationsDIN 43625

VDE 0670-4

IEC 60282-1Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)Rated current25 ARated voltage7.2

kVVoltage typeACRated frequency50 - 50 HzBreaking capacity63 kAUtilization categoryOtherApplicationMotor

protectionLength530 mmDiameter76 mmPerformance category according to IEC 60282-1Back-upWith

strikerYesStandardDINRelease characteristicOtherInstallation techniqueAir

ETIM for 7.2WFMSSJ125 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

25 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.063 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Motor protection

Length (EF001438)

442 mm

Diameter (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 125amps"MOTOR START FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.