

INDUSTRIAL COMPONENT DATA

7.2KV 25AMP 2" AIR FUSE DCR 3565 7.2BDGHO25 EATON

ELECTRIC Air fuse-link, medium voltage, 25 A, AC 7.2 kV, 4..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 25AMP 2" AIR FUSE DCR 3565



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 25AMP 2" AIR FUSE DCR 3565
Catalog number	72BDGHO25
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-1A6944D906
Generated	2026-08-06

Product Overview

Air fuse-link, medium voltage, 25 A, AC 7.2 kV, 441 x 50.8 mm, back-up, BS, with striker

Air fuse cartridge, MT, 25 A, AC 7.2 kV, 441 x 50.8 mm, back-up, BS, with striker

Fuse, Air fuse-link, medium voltage, 25 A, AC 7.2 kV, 441 x 50.8 mm, back-up, BS, with striker, cylindrical, offset bolted tags, protection of primary side transformers, used in fuse switch combination units, fuse bases and fuse switches, BS2962-1, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Air fuse-link, medium voltage, 25 A, AC 7.2 kV, 441 x 50.8 mm, back-up, BS, with striker Fuse, Air fuse-link, medium voltage, 25 A, AC 7.2 kV, 441 x 50.8 mm, back-up, BS, with striker, cylindrical, offset bolted tags, protection of primary side transformers, used in fuse switch combination units, fuse bases and fuse switches, BS2962-1, Breaking Capacity 40 kA Delivery program

Product range Fuse Basic function Air fuse-link Field of application medium voltage Rated current [I] 25 A Rated voltage AC 7.2 kV Size 441 x 50.8 mm Utilization category back-up Status indicator with striker Breaking Capacity 40 kA usable for size/applications protection of primary side transformers

used in fuse switch combination units, fuse bases and fuse switches Standard/Approval BS Shape cylindrical offset bolted tags Standards/Regulations BS2962-1 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 25 A Rated voltage 7.2 kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 40 kA Utilization category Other Application Primary side

transformer protection Length 359 mm Diameter 51 mm Performance category according to IEC 60282-1 Back-up With
striker Yes Standard British Standard Release characteristic Other Installation technique Air
ETIM for 7.2BDGHO25 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

25 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 25AMP 2" AIR FUSE DCR 3565 with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.