

INDUSTRIAL COMPONENT DATA

**7.2KV 2X250A M/S 1241 7.2WKNHO2 2X250 3.6WKFHO22X250
EATON ELECTRIC Motor fuse-link, medium voltage, 450 A, ..**

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 2X250A M/S 1241



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 2X250A M/S 1241
Catalog number	3.6WKFHO22X250
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-DAF780A335
Generated	2026-08-06

Product Overview

Motor fuse-link, medium voltage, 450 A, AC 3.6 kV, 76 x 254 mm, back-up, BS, with striker

Motor cartridge fuse, MT, 450 A, AC 7.2 kV, 76 x 403mm, back-up, BS, with striker

7.2WKNHO2 2X250 - Motor fuse-link, medium voltage, 450 A, AC 7.2 kV, 76 x 403mm, back-up, BS, with striker

Fuse, Motor fuse-link, medium voltage, 450 A, AC 7.2 kV, 76 x 403mm, back-up, BS, with striker, cylindrical, offset bolted tags, dual-barrel, motor protection, BS2692-1, IEC 60282-1, Breaking Capacity 40 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 450 A, AC 7.2 kV, 76 x 403mm, back-up, BS, with striker Fuse, Motor fuse-link, medium voltage, 450 A, AC 7.2 kV, 76 x 403mm, back-up, BS, with striker, cylindrical, offset bolted tags, dual-barrel, motor protection, BS2692-1, IEC 60282-1, Breaking Capacity 40 kA Delivery program

Product range Fuse Basic function Motor fuse-link Field of application medium voltage Rated current [I] 450 A Rated voltage AC 7.2 kV Size 76 x 403mm Utilization category back-up Status indicator with striker Description dual-barrel Breaking Capacity 40 kA usable for size/applications motor protection Standard/Approval BS Shape cylindrical offset bolted tags Standards/Regulations BS2692-1

IEC 60282-1 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 250 A Rated voltage 7.2 kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 40 kA Utilization category Other Application Motor protection Length 486 mm Diameter 76 mm Performance category according to IEC 60282-1 Back-up With striker Yes

Standard British Standard Release characteristic Other Installation technique Air
ETIM for 7.2WKNHO2 2X250 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

250 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.04 kA

Utilization category according to IEC 60269 (EF002572)

Other

Length (EF001438)

486 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 2X250A M/S 1241 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.