

INDUSTRIAL COMPONENT DATA

7.2KV 355A 3" MOTORSTART FUSE 7.2WKMSJ355

7-2WKMSJ355 EATON ELECTRIC Motor cartridge fuse, MT, 355, AC 7.2 k..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 355A 3" MOTORSTART FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 355A 3" MOTORSTART FUSE
Catalog number	7-2WKMSJ355
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-A632C7754B
Generated	2026-08-06

Product Overview

Motor cartridge fuse, MT, 355, AC 7.2 kV, DIN43625 3", 76 x 442 mm, back-up, DIN, with striker

7.2KV 355Amp 3" MOTORSTART FUSE

7.2KV 355Amp 3" MOTORSTART FUSE - Motor fuse-link, medium voltage, 355 A, AC 7.2 kV, 63 kA, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker

Fuse, Motor fuse-link, medium voltage, 355 A, AC 7.2 kV, DIN 43625 3z, 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Busmann series medium voltage motor fuse Catalog Number 7.2WKMSJ355 Model Code 7.2KV 355A 3" MOTORSTART FUSE EAN 5027590054720 UPC 051712837828 Product Length/Depth 442 mm Product Height 76 mm Product Width 76 mm Product Weight 5200 g Compliances VDE 0670-4

DIN 43625 Certifications IEC60282-1 Product specifications

Used with A3354730 Nickel-plated copper fuse clip Type fuse Application Motor protection Amperage Rating 355 A Fuse indicator Non Indicating Fuse size 76 x 442 mm Breaking capacity 63 A Installation technique Air Performance Cat According To IEC 60282-1 Back-up Product application Motor protection Rated frequency - max 50 Hz Rated frequency -

min 50 Hz Release characteristic Other Standard DIN Utilization category Other Voltage type AC With striker Yes Class
Class back-up Barrels 1 Fuse shape Cylindrical Watt losses 125 W Resistance 0.72 ohms Fuse diameter 76 mm Interrupt
rating 63 kAIC Construction size 76 x 442 mm Packaging type Standard Voltage rating 7.2 kV Fuse type WKMSJ
ETIM for 7.2WKMSJ355 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

355 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.063 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Motor protection

Length (EF001438)

442 mm

Diameter (EF000551)

76 mm

Performance category according to IEC 60282-1 (EF01253...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 355A 3" MOTORSTART FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.