

INDUSTRIAL COMPONENT DATA

7.2KV 40AMP 3" M/START 7.2WFMSJ40 7-2WFMSJ40 EATON ELECTRIC Motor fuse-link, medium voltage, 40 A, AC 7.2 kV..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 40AMP 3" M/START



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 40AMP 3" M/START
Catalog number	7-2WFMSJ40
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-3682CEC100
Generated	2026-08-06

Product Overview

Motor fuse-link, medium voltage, 40 A, AC 7.2 kV, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker
Fuse cartridge motor, MT, 40 A, AC 7.2 kV, DIN43625 3", 76 x 442 mm, back-up, DIN, with striker
Fuse, Motor fuse-link, medium voltage, 40 A, AC 7.2 kV, DIN 43625 3z, 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 40 A, AC 7.2 kV, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker Fuse, Motor fuse-link, medium voltage, 40 A, AC 7.2 kV, DIN 43625 3", 76 x 442 mm, back-up, DIN, with striker, cylindrical, motor protection, DIN 43625, VDE 0670-4, IEC 60282-1, Breaking Capacity 63 kA Delivery program
Product range Fuse Basic function Motor fuse-link Field of application medium voltage Rated current [I] 40 A Rated voltage AC 7.2 kV Construction size DIN 43625 3" Size 76 x 442 mm Utilization category back-up Status indicator with striker Breaking Capacity 63 kA usable for size/applications motor protection Standard/Approval DIN Shape cylindrical Standards/Regulations DIN 43625 VDE 0670-4 IEC 60282-1 Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 40 A Rated voltage 7.2 kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 63 kA Utilization category Other Application Motor protection Length 530 mm Diameter 76 mm Performance category according to IEC 60282-1 Back-up With striker Yes

Standard DIN Release characteristic Other Installation technique Air
ETIM for 7.2WFMSJ40 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

40 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.063 kA

Utilization category according to IEC 60269 (EF002572)

Other

Length (EF001438)

76 mm

Performa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 40AMP 3" M/START with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.