

INDUSTRIAL COMPONENT DATA

7.2KV 50AMP 3" MOTORSTART FUSE 7.2WFMH750

7-2WFMH750 EATON ELECTRIC Motor fuse-link, medium voltage, 50 A, A..

Brand: EATON - MOELLER | Manufacturer Part Number: 7.2KV 50AMP 3" MOTORSTART FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	7.2KV 50AMP 3" MOTORSTART FUSE
Catalog number	7-2WFMH750
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-9B76CE4B8D
Generated	2026-08-06

Product Overview

Motor fuse-link, medium voltage, 50 A, AC 7.2 kV, 76 x 442 mm, back-up, BS, 3E, with striker

7.2KV 50AMP 3" MOTORSTART FUSE

7.2KV 50AMP 3" MOTORSTART FUSE - Motor fuse-link, medium voltage, 50 A, AC 7.2 kV, 63 kA, 76 x 442 mm, back-up, BS, with striker, 3E

Fuse, Motor fuse-link, medium voltage, 50 A, AC 7.2 kV, 76 x 442 mm, back-up, BS, 3E, with striker, cylindrical, offset bolted tags, motor protection, BS2692-1, IEC 60282-1, Breaking Capacity 63 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 50 A, AC 7.2 kV, 63 kA, 76 x 442 mm, back-up, BS, with striker, 3E
Fuse, Motor fuse-link, medium voltage, 50 A, AC 7.2 kV, 76 x 442 mm, back-up, BS, 3E, with striker, cylindrical, offset bolted tags, motor protection, BS2692-1, IEC 60282-1, Breaking Capacity 63 kA
Delivery program

Product range Fuse
Basic function Motor fuse-link
Field of application medium voltage
Rated current [I] 50 A
Rated voltage AC 7.2 kV
Size 76 x 442 mm
Utilization category back-up
Status indicator with striker
Breaking Capacity 63 kA
Usable for size/applications motor protection
Release characteristic [class] 3E
Standard/Approval BS
Shape cylindrical
offset bolted tags
Standards/Regulations BS2692-1

IEC 60282-1
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 50 A Rated voltage 7.2 kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 63 kA Utilization category Other Application Motor protection Length 442 mm Diameter 76 mm Performance category according to IEC 60282-1 Back-up With striker Yes Standard DIN Release characteristic Other Installation technique Air ETIM for 7.2WFMH750 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

50 A

Rated voltage (EF000228)

7.2 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.063 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Motor protection

Length (EF001438)

442 mm

Diameter (EF000551)

76 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 7.2KV 50AMP 3" MOTORSTART FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.