

INDUSTRIAL COMPONENT DATA

75A 690V AC TYPE T FUSE 75EET EATON ELECTRIC

Expulsion fuse-link, medium voltage, 5 A, AC 15 kV, 533 mm, ANS..

Brand: EATON - MOELLER | Manufacturer Part Number: 75A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	75A 690V AC TYPE T FUSE
Catalog number	75EET
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-24E17CD523
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 5 A, AC 15 kV, 533 mm, ANSI, T slow, style B termination

75A 690V AC TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Double barrel, 75A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 75 A, AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0122

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 75EET Model Code 75A 690V AC TYPE T FUSE EAN 5027590489140 UPC 051712837248 Product Length/Depth 94 mm Product Height 36 mm Product Width 20 mm Product Weight 91.6 g Compliances RoHS Compliant

CE Electrical data

Amperage Rating 75 A Voltage rating 690 V (IEC), 700 V (UL) Rated voltage AC 690 V Rated voltage DC 500 V Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Class Class aR Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None Compatble Trip indicator/Microswitch

Suitable for EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

ETIM for 75EET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

690 V

Rated voltage DC (EF012281)

500 V

Rated current (EF000227)

75 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

71 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 75A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.