

INDUSTRIAL COMPONENT DATA

800A 415V AC TYPE J FUSE 800SJ28 EATON ELECTRIC

Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 31 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 800A 415V AC TYPE J FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	800A 415V AC TYPE J FUSE
Catalog number	800SJ28
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-4352779CB5
Generated	2026-08-06

Product Overview

Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 31 x 110 mm, gL/gG, BS, 82mm fixing centres

800A 415V AC TYPE J FUSE

Fuse-link, low voltage, 800 A, AC 415 V, 80 kA, BS88/J, 73 x 129 mm, gL/gG, BS, 92 mm fixing centres

Fuse, Utility fuse-link, low voltage, 800 A, AC 415 V, BS88/J, 73 x 129 mm, gU, BS, dual bolted tags, 92mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 800 A, AC 415 V, 80 kA, BS88/J, 73 x 129 mm, gL/gG, BS, 92 mm fixing centres
Fuse, Utility fuse-link, low voltage, 800 A, AC 415 V, BS88/J, 73 x 129 mm, gL/gG, BS, dual bolted tags, 92mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW4
Delivery program
Product range Fuse
Basic function Utility fuse-link
Field of application low voltage
Rated current [I]
800 A
Rated voltage AC 415 V
Construction size BS88/J
Size 73 x 129 mm
Utilization category gL/gG
Description 92 mm fixing centres
Breaking Capacity 80 kA
Usable for size/applications feeder pillars
Standard/Approval BS
Shapedual bolted tags
Standards/Regulations BS88-2 IEC 60269-2
Optional accessories fuse-holder JW4
Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size Other
Rated current 800 A
Rated voltage 415 V
Voltage type AC
Rated switching capacity 80 kA
Utilization category Other
Type of fuse status indicator None
Insulated metal gripping lugs (IMGL) No

ETIM for 800SJ28 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

J

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

800 A

Uti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 800A 415V AC TYPE J FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.