

INDUSTRIAL COMPONENT DATA

80A 1500V AC 660V DC BS88 FUSE TFC80 EATON ELECTRIC

Fuse-link, low voltage, 50 A, AC 660 V, DC 460 V, BS88/A..

Brand: EATON - MOELLER | Manufacturer Part Number: 80A 1500V AC 660V DC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	80A 1500V AC 660V DC BS88 FUSE
Catalog number	TFC80
Category	HRC fuse
Minimum order	6 Pcs
Document ID	EO-D935E91952
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 50 A, AC 660 V, DC 460 V, BS88/A4, 26 x 110 mm, gL/gG, BS

80A 1500V AC 660V DC BS88 FUSE

Fuse-link, low voltage, 80 A, AC 1500 V, DC 660 V, 40 x 192 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 80 A, AC 1500 V, DC 660 V, 40 x 192 mm, gL/gG, BS, offset bolted tags, BS2692, IEC 60269-1, Breaking Capacity 63 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Busmann series low voltage british standard fuse Catalog Number TFC80 EAN 5027590568876
UPC 051712392860 Product Length/Depth 215 mm Product Height 47 mm Product Width 48 mm Product Weight 90.5 g
Compliances Contact Manufacturer Electrical data

Amperage Rating 80 A Voltage rating 1500 V Voltage type AC/DC Breaking capacity 63 kA Class Class gG/gL Product specifications

Fuse type TFC

ETIM for TFC80 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

1500 V

Rated voltage DC (EF012281)

660 V

Rated current (EF000227)

80 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

63 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

168.4 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 80A 1500V AC 660V DC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.