

INDUSTRIAL COMPONENT DATA

80AMP 240V AC BS88 FUSE 80LET EATON ELECTRIC

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm..

Brand: EATON - MOELLER | Manufacturer Part Number: 80AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	80AMP 240V AC BS88 FUSE
Catalog number	80LET
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-64E6F9E0D9
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS

80AMP 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 80A, 280 VAC/150 VDC (UL), Class aR, 200 kA RMS Sym., Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

Fuse, Fuse-link, high speed, 80 A, AC 240 V, DC 150 V, BS88, 18 x 56 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 80LET EAN 5027590490610 UPC 051712838047 Product Length/Depth 55 mm Product Height 18 mm Product Width 18 mm Product Weight 32 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4 Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 80 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 280 V
Rated voltage DC 150 V Center-to-center distance of connections 41 mm Mounting dimension M6 Current type AC/DC
Class Class aR Clearing (I₂T) 3800 Watt losses 10 W Fuse shape Offset bolted tags Pre arc (I₂T) 300 Color None Interrupt
rating 200 kA RMS Sym, 50 kA DC at 150 Vdc Connection Blade end x blade end Construction size Other Mounting
method Stud Packaging type Standard Voltage rating 280 V Fuse type LET Suitable for TI500 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 80LET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 80AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.