

INDUSTRIAL COMPONENT DATA

80AMP 700V AC SEMI-COND FUSE FWP-80B EATON

ELECTRIC cartridge fuse, ultra rapid, 80 A, AC 700 V DC 700 V, 25..

Brand: EATON - MOELLER | Manufacturer Part Number: 80AMP 700V AC SEMI-COND FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	80AMP 700V AC SEMI-COND FUSE
Catalog number	FWP-80B
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-30C6C4E38A
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 80 A, AC 700 V DC 700 V, 25 x 112 mm, aR, UL

80AMP 700V AC SEMI-COND FUSE

80AMP 700V AC SEMI-COND FUSE - Fuse-link, high speed, 80 A, AC 700 V, DC 700 V, 200 kA, 25 x 112 mm, aR, UL

Fuse, Fuse-link, high speed, 80 A, AC 700 V, DC 700 V, 25 x 112 mm, aR, UL, centre-bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder BH series

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 80 A, AC 700 V, DC 700 V, 200 kA, 25 x 112 mm, aR, UL
Fuse, Fuse-link, high speed, 80 A, AC 700 V, DC 700 V, 25 x 112 mm, aR, UL, centre-bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder BH series
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 80 A
Rated voltage AC 700 V
DC 700 V
Size 25 x 112 mm
Utilization category aR
Breaking Capacity 200 kA
Usable for size/applications protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval UL
Shape centre-bolted tags
Standards/Regulations UL 248
Optional accessories fuse-holder BH series
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 80 A Rated voltage 700 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No ETIM for FWP-80B Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF0076...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 80AMP 700V AC SEMI-COND FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.