

INDUSTRIAL COMPONENT DATA

93E30KMBSB EATON ELECTRIC Eaton 93E UPS, Tower Online UPS, 30 kVA, 3 phase in/3 phase out, Power factor 0,9,..

Brand: EATON - MOELLER | Manufacturer Part Number: 93E30KMBSB



Manufacturer	EATON - MOELLER
MPN / Reference	93E30KMBSB
Catalog number	10000
Category	UPS
Minimum order	1 Pcs
Document ID	EO-AAE5932658
Generated	2026-08-04

Product Overview

Eaton 93E UPS, Tower Online UPS, 30 kVA, 3 phase in/3 phase out, Power factor 0,9, Internal Maintenance Bypass Switch, 93E 30kVA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 93E UPS Catalog Number 93E30KMBSB EAN 3553340693052 Product Length/Depth 1 m Product Height 1 m Product Width 0.001 m Product Weight 0.001 kg Compliances CE Marked

RoHS Compliant

CB Certifications IEC/EN 62040-2

IEC/EN 62040-1

EN 62040-3

Manufactured in a plant certified to ISO 9001 and ISO 14001 management system standards Product specifications

Type UPS Audible alarms Yes Auto shutdown function Yes Internal battery included No, kits available User replaceable

batteries No Battery charger type ABM technology External battery connection Hardwired Color Black Construction type

Free standing model Efficiency (eco-mode) 98 % Improved efficiency mode High Efficiency Number of communication slots

2 Feed type AC Form factor Tower Hot-swappable power modules No Input connection Fixed connection Input nominal

voltage 400V default (380/400/415V) Number of output connections fixed connection 1 Output frequency 50 Hz (50/60 Hz programmable) Output power factor .9 Overall efficiency 94 % Package contents Parallelable Parallel for capacity and redundancy Number of parallel units 4 Phase (input) 3 Phase (output) 3 Potential free switch contact No Snmp No Start-on-battery No Topology Online Type Of Interface Other Internal maintenance bypass Yes User Interface (Hmi) Graphical LCD kVA rating 30 kVA Wattage 27 kW Application Data center/ facility/IT Output effective power 27000 W Transition time for full load 0 s Efficiency (improved efficiency mode)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 93E30KMBSB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.