

INDUSTRIAL COMPONENT DATA

93E80KMBSN EATON ELECTRIC Eaton 93E UPS, Tower Online UPS, 80 kVA, 3 phase in/3 phase out, Power factor 0,9,..

Brand: EATON - MOELLER | Manufacturer Part Number: 93E80KMBSN



Manufacturer	EATON - MOELLER
MPN / Reference	93E80KMBSN
Catalog number	10000
Category	UPS
Minimum order	1 Pcs
Document ID	EO-590D870268
Generated	2026-08-04

Product Overview

Eaton 93E UPS, Tower Online UPS, 80 kVA, 3 phase in/3 phase out, Power factor 0,9, 93E 80kVA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

General specifications

Product Name Eaton 93E UPS Catalog Number 93E80KMBSN EAN 3553340693007 Product Length/Depth 800 mm

Product Height 1880 mm Product Width 600 mm Product Weight 245 kg Compliances CE Marked

RoHS Compliant

CB Certifications IEC/EN 62040-2

IEC/EN 62040-1

EN 62040-3

Manufactured in a plant certified to ISO 9001 and ISO 14001 management system standards Product specifications

Type UPS Audible alarms Yes Auto shutdown function Yes Battery charger type ABM technology External battery

connection Hardwired Color Black Construction type Free standing model Efficiency (eco-mode) 98 % Improved efficiency

mode High Efficiency Feed type AC Form factor Tower Hot-swappable power modules No Input connection Fixed

connection Input nominal voltage 400V default (380/400/415V) Number of output connections fixed connection 1 Output

frequency 50 Hz (50/60 Hz programmable) Output power factor .9 Overall efficiency 94 % Package contents Parallelable

Parallel for capacity and redundancy Phase (input) 3 Phase (output) 3 Potential free switch contact No Snmp No Topology
Online Type Of Interface Other Internal maintenance bypass No kVA rating 80 kVA Wattage 72000 W Application Data
center/ facility/IT Output effective power 72 kW Transition time for full load 0 s Efficiency (improved efficiency mode) 0.98 %
Voltage distortion output (linear load) - max 2 % Integrated functionality Network Mangement Input frequency - min 50 Hz
Input frequency - max 60 Hz Input voltage - min 380 V Inp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 93E80KMBSN with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.