

INDUSTRIAL COMPONENT DATA

Eaton 9E 6000i 9E6KI 9104-12759 EATON ELECTRIC 9E 6000i UNINTERRUPTIBLE POWER SUPPLY ONLINE DOUBLE CONVERSI..

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9E 6000i



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9E 6000i
Catalog number	9104-12759
Category	UPS
Minimum order	1 Pcs
Document ID	EO-6E76A6A8A7
Generated	2026-08-04

Product Overview

9E 6000i UNINTERRUPTIBLE POWER SUPPLY ONLINE DOUBLE CONVERSION, SUPPLY INPUT/OUTPUT VOLTAGE 220-240V, MAX CURRENT 82A, POWER 6000VA/4800W, 0-40 DEGC; 3 OUTLET; 708.5MM x 262.4MM x 612.9MM (HxWxL); TOWER FORMAT

Eaton 9E 6000i

Eaton 9E UPS, 6000 VA, 4800 W, Input: Hardwired, Output: Hardwired, Tower

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Single-phase UPS up to 11kVA
--------------	--

Additional Product Information

General specifications

Product Name Eaton 9E UPS Catalog Number 9E6KI UPC 743172067661 Product Length/Depth 61.29 cm Product Height 70.85 cm Product Width 26.24 cm Product Weight 68 kg Compliances CE Marked

TUV Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Product specifications

Special features Type UPS Topology Online/Double-conversion Form factor Tower Construction type Free standing model Color Black VA rating 6000 VA Wattage 4800 W Rack mounting kit No Package contents UPS

USB cable

Serial cable

User manual

Internal bypass Yes Hot swap power No Auto shutdown function Yes Primary frequency - max 66 Hz Primary frequency - min 45 Hz Input connection Hardwired/fixed connection Input nominal voltage 230V default (220/230/240V) Nominal frequency 50/60 Hz Input frequency range 45-66Hz Input power factor >.99 Number of outputs hardwired 1 Output waveform Sine wave Voltage 230V Output nominal voltage 230V default (220/230/240V) Feed type 1 Voltage type AC

Runtime graph Battery management Automatic battery test

Deep discharge protection

Battery replacement Replacable batteries Battery rating 12 V / 9 Ah Battery type Sealed, lead-acid Extended battery capability Yes Runtime at half load 10 min Communication USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for remote power off

Communication slot

Expansion slots One slot for optional communication card Ethernet interface No Includes network card No Software compatibility Eaton Intelligent Power Manager, Eaton I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9E 6000i with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.