

INDUSTRIAL COMPONENT DATA

Eaton 9PX 1000i RT2U 9PX1000IRT2U 9103-53748 EATON ELECTRIC Eaton 9PX 1000i RT2U

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 1000i RT2U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 1000i RT2U
Catalog number	9103-53748
Category	UPS
Minimum order	1 Pcs
Document ID	EO-A4E60EE366
Generated	2026-08-03

Product Overview

Eaton 9PX 1000i RT2U

Eaton 9PX UPS, 1000 VA, 1000 W, Input: C14, Outputs: (8) C13, Rack/tower, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX1000IRT2U UPC 743172081407 Product Length/Depth 45 cm Product Height 8.65 cm Product Width 44 cm Product Weight 17.4 kg Warranty 3 year on electronics, 2 year on battery

Compliances CE Marked

TUV

cULus Listed

CSA 22.2

FCC part 15 Class B

CISPR22 Class B Certifications IEC/EN 62040-1

UL 1778

IEC/EN 62040-2

CE

cULus Listed

EAC

ENERGY STAR certified Battery

Runtime graph View runtime graph Battery management Battery replacement Hot-swappable internal batteries and extended battery modules (EBMs) Battery quantity 4 Battery rating 12 V / 7 Ah Battery type Sealed, lead-acid Extended battery capability Yes Electrical output

Receptacle (8) C13 Topology Online/Double-conversion Wattage 1000 W VA rating 1000 VA Output waveform Sine wave Voltage 230V Output power factor 1 Output nominal voltage 230V default (200/208/220/230/240V) Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 3 Output frequency 50/60 Hz Feed type 1

Electrical input

Input connection C14 Input nominal voltage 230V default (200/208/220/230/240V) Input voltage range 176-276 V (100-276 V with derating) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Communications

Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Mini-terminal block for output relay

Dry contacts (3 outputs, 1 input, optoco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 1000i RT2U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.