

INDUSTRIAL COMPONENT DATA

Eaton 9PX 2200i RT3U HotSwap IEC 9PX2200IRTBP 9103-73789-KT5 EATON ELECTRIC Eaton 9PX 2200i RT3U HotSwap IEC

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 2200i RT3U HotSwap IEC



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 2200i RT3U HotSwap IEC
Catalog number	9103-73789-KT5
Category	UPS
Minimum order	1 Pcs
Document ID	EO-55EB061C7A
Generated	2026-08-04

Product Overview

Eaton 9PX 2200i RT3U HotSwap IEC

Eaton 9PX UPS HotSwap IEC, 2200 VA, 2200 W, Input: C20, Outputs: (6) C13, (1) C19, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

Eaton 9PX 2200i RT3U HotSwap IEC Eaton 9PX 2200i RT3U HotSwap IEC, 2200 VA, 2200 W, Input: C20, Outputs: (6) C13, (1) C19, Rack/tower, 3U Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382) Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) ( [BAB258012])

Input voltage 100 - 276 V Primary frequency 40 - 70 Hz Number of phases primary 1 Output voltage 200 - 240 V Secondary frequency 50 - 60 Hz Output effective power 2200 W Output apparent power 2200 VA Type of interface Other Number of phases secondary 1 SNMP Yes Voltage type AC Height 130 mm Width 440 mm Depth 485 mm Transition time for full load 3.5 min Weight 24.5 kg Network-management Yes USV- technology Online Construction type 482.6 mm (19 inch) device Max. voltage distortion output (linear load) 2 % Output power factor 1 Overall efficiency 93.5 % Efficiency in eco-mode 98 % Potential free switch contact Yes Auto shut down function Yes Input connection C20 Number of output connections C13 6 Number of output connections C19 1 Number of output connections with protective contact (SCHUKO) 0 Number of output connections fixed connection 0

ETIM for 9PX2200IRTBP Data networking products (EC000382)

Feature Name

Feature Value

Input voltage (EF003840)

100 V

Primary frequency (EF009272)

40 Hz

Number of phases primary (EF009275)

1

Output voltage (EF003933)

200 V

Secondary frequency (EF009273)

50 Hz

Output effective power (EF009897)

22...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 2200i RT3U HotSwap IEC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.