

## INDUSTRIAL COMPONENT DATA

# Eaton 9PX 2200i RT3U HotSwap DIN 9PX2200IRTBDP 9103-73789-KT2 EATON ELECTRIC Eaton 9PX 2200i RT3U HotSwap DIN

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 2200i RT3U HotSwap DIN



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | EATON - MOELLER                  |
| MPN / Reference | Eaton 9PX 2200i RT3U HotSwap DIN |
| Catalog number  | 9103-73789-KT2                   |
| Category        | UPS                              |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-8BE6F744A7                    |
| Generated       | 2026-08-04                       |

## Product Overview

Eaton 9PX 2200i RT3U HotSwap DIN

Eaton 9PX 2200i RT3U HotSwap DIN - Eaton 9PX 2200i RT3U HotSwap DIN

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog pathEATON - MOELLER &gt; Single-phase UPS up to 11kVA

## Additional Product Information

Eaton 9PX 2200i RT3U HotSwap DIN Eaton 9PX 2200i RT3U HotSwap DIN, 2200 VA, 2200 W, Input: C20, Outputs: (4) Schuko, (1) C19, Rack/tower, 3U Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382) Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) ([email protected] [BAB258012])

Input voltage100 - 276 VPrimary frequency40 - 70 HzNumber of phases primary1Output voltage200 - 240 VSecondary frequency50 - 60 HzOutput effective power2200 WOutput apparent power2200 VAType of interfaceOtherNumber of phases secondary1SNMPYesVoltage typeACHeight130 mmWidth440 mmDepth485 mmTransition time for full load3.5 minWeight24.5 kgNetwork-managementYesUSV- technologyOnlineConstruction type482.6 mm (19 inch) deviceMax. voltage distortion output (linear load)2 %Output power factor1Overall efficiency93.5 %Efficiency in eco-mode98 %Potential free switch contactYesAuto shut down functionYesInput connectionC20Number of output connections C130Number of output connections C191Number of output connections with protective contact (SCHUKO)4Number of output connections fixed connection0

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 2200i RT3U HotSwap DIN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.