

INDUSTRIAL COMPONENT DATA

Eaton 9PX 2200i RT3U HotSwap HW 9PX2200IRTBPH 9103-73789-KT4 EATON ELECTRIC Eaton 9PX 2200i RT3U HotSwap HW

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 2200i RT3U HotSwap HW



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 2200i RT3U HotSwap HW
Catalog number	9103-73789-KT4
Category	UPS
Minimum order	1 Pcs
Document ID	EO-E4E260C91E
Generated	2026-08-04

Product Overview

Eaton 9PX 2200i RT3U HotSwap HW

Eaton 9PX 2200i RT3U HotSwap HW - Eaton 9PX 2200i RT3U HotSwap HW

Eaton 9PX UPS HotSwap HW, 2200 VA, 2200 W, Input: Hardwired, Outputs: Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

Eaton 9PX 2200i RT3U HotSwap HWEaton 9PX 2200i RT3U HotSwap HW, 2200 VA, 2200 W, Input: Fixed connection, Outputs: Hardwired, Rack/tower, 3UTechnical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) ( [BAB258012])Input voltage100 - 276 VPrimary frequency40 - 70 HzNumber of phases primary1Output voltage200 - 240 VSecondary frequency50 - 60 HzOutput effective power2200 WOutput apparent power2200 VAType of interfaceOtherNumber of phases secondary1SNMPYesVoltage typeACHeight130 mmWidth440 mmDepth485 mmTransition time for full load3.5 minWeight24.5 kgNetwork-managementYesUSV- technologyOnlineConstruction type482.6 mm (19 inch) deviceMax. voltage distortion output (linear load)2 %Output power factor1Overall efficiency93.5 %Efficiency in eco-mode98 %Potential free switch contactYesAuto shut down functionYesInput connectionFixed connectionNumber of output connections C130Number of output connections C190Number of output connections with

protective contact (SCHUKO)0Number of output connections fixed connection1

ETIM for 9PX2200IRTBPB Data networking products (EC000382)

Feature Name

Feature Value

Input voltage (EF003840)

100 V

Primary frequency (EF009272)

40 Hz

Number of phases primary (EF009275)

1

Output voltage (EF003933)

200 V

Secondary frequency (EF009273)

50 Hz

Output effective p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 2200i RT3U HotSwap HW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.