

INDUSTRIAL COMPONENT DATA

Eaton 9PX 3000i RT2U 9PX3000IRT2U 9103-83800 EATON ELECTRIC Eaton 9PX 3000i RT2U

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 3000i RT2U



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 3000i RT2U
Catalog number	9103-83800
Category	UPS
Minimum order	1 Pcs
Document ID	EO-1C6FBBBD63
Generated	2026-08-05

Product Overview

Eaton 9PX 3000i RT2U

Eaton 9PX UPS, 3000 VA, 3000 W, Input: C20, Outputs: (8) C13, (2) C19, Rack/tower, 2U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

Eaton 9PX 3000i RT2UEaton 9PX 3000i RT2U, 3000 VA, 3000 W, Input: C20, Outputs: (8) C13, (2) C19, Rack/tower, 2U
Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382)Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) () [BAB258012])Input voltage100 - 276 VPrimary frequency40 - 70 HzNumber of phases primary1Output voltage200 - 240 VSecondary frequency50 - 60 HzOutput effective power3000 WOutput apparent power3000 VAType of interfaceOtherNumber of phases secondary1SNMPYesVoltage typeACHeight86.5 mmWidth440 mmDepth605 mmTransition time for full load3 minWeight27.5 kgNetwork-managementYesUSV- technologyOnlineConstruction type482.6 mm (19 inch) deviceMax. voltage distortion output (linear load)2 %Output power factor1Overall efficiency94 %Efficiency in eco-mode98 %Potential free switch contactYesAuto shut down functionYesInput connectionC20Number of output connections C138Number of output connections C192Number of output connections with protective contact (SCHUKO)0Number of output connections fixed connection0

ETIM for 9PX3000IRT2U Data networking products (EC000382)

Feature Name

Feature Value

Input voltage (EF003840)

100 V

Primary frequency (EF009272)

40 Hz

Number of phases primary (EF009275)

1

Output voltage (EF003933)

200 V

Secondary frequency (EF009273)

50 Hz

Output effective power (EF009897)

3000 W

Output apparent power....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 3000i RT2U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.