

INDUSTRIAL COMPONENT DATA

Eaton 9PX 3000i RT3U HotSwap DIN 9PX3000IRTBDP EATON ELECTRIC Eaton 9PX 3000i RT3U HotSwap DIN

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 3000i RT3U HotSwap DIN



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 3000i RT3U HotSwap DIN
Catalog number	9103-83805-KT2
Category	UPS
Minimum order	1 Pcs
Document ID	EO-3642632333
Generated	2026-08-05

Product Overview

Eaton 9PX 3000i RT3U HotSwap DIN

Eaton 9PX 3000i RT3U HotSwap DIN - Eaton 9PX 3000i RT3U HotSwap DIN

Eaton 9PX UPS HotSwap DIN, 3000 VA, 3000 W, Input: C20, Outputs: (4) Schuko, (1) C19, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Single-phase UPS up to 11kVA

Additional Product Information

Eaton 9PX 3000i RT3U HotSwap DIN Eaton 9PX 3000i RT3U HotSwap DIN, 3000 VA, 3000 W, Input: C20, Outputs: (4) Schuko, (1) C19, Rack/tower, 3U Technical data ETIM 7.0

Data and telecommunication (EG000037) / UPS (EC000382) Electric engineering, automation, process control engineering / Power supply devices / No-break power supply (complete) / No-break power supply (complete, unspecified) ( [BAB258012]) Input voltage 100 - 276 V Primary frequency 40 - 70 Hz Number of phases primary 1 Output voltage 200 - 240 V Secondary frequency 50 - 60 Hz Output effective power 3000 W Output apparent power 3000 VA Type of interface Other Number of phases secondary 1 SNMP Yes Voltage type AC Height 130 mm Width 440 mm Depth 485 mm Transition time for full load 3 min Weight 27.5 kg Network-management Yes USV- technology Online Construction type 482.6 mm (19 inch) device Max. voltage distortion output (linear load) 2 % Output power factor 1 Overall efficiency 94 % Efficiency in eco-mode 98 % Potential free switch contact Yes Auto shut down function Yes Input connection C20 Number of output connections C130 Number of output connections C191 Number of output connections with protective contact (SCHUKO) 4 Number of output connections fixed connection 0

ETIM for 9PX3000IRTBDP Data networking products (EC000382)

Feature Name

Feature Value

Input voltage (EF003840)

100 V

Primary frequency (EF009272)

40 Hz

Number of phases primary (EF009275)

1

Output voltage (EF003933)

200 V

Secondary frequency (EF009273)

50 Hz

Output effective power (EF009897)

30...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 3000i RT3U HotSwap DIN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.