

INDUSTRIAL COMPONENT DATA

Eaton 9PX 3000i RT3U HotSwap HW 9PX3000IRTBPH EATON ELECTRIC Eaton 9PX 3000i RT3U HotSwap HW

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 3000i RT3U HotSwap HW



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 3000i RT3U HotSwap HW
Catalog number	9103-83805-KT4
Category	UPS
Minimum order	1 Pcs
Document ID	EO-44487C8AE2
Generated	2026-08-03

Product Overview

Eaton 9PX 3000i RT3U HotSwap HW

Eaton 9PX UPS HotSwap HW, 3000 VA, 3000 W, Input: Hardwired, Outputs: Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX3000IRTBPH Model Code Eaton 9PX 3000i RT3U HotSwap HW UPC 743172081599 Product Length/Depth 48.5 cm Product Height 13 cm Product Width 44 cm Product Weight 27.41 kg

Warranty 3 year on electronics, 2 year on battery Compliances CE Marked

TUV

cULus Listed

CSA 22.2

FCC part 15 Class B

CISPR22 Class B Certifications EAC

CE

ENERGY STAR certified

IEC/EN 62040-1

UL 1778

IEC/EN 62040-2 Battery

Runtime graph View runtime graph Battery management Battery replacement Hot-swappable internal batteries and extended battery modules (EBMs) Battery quantity 6 Battery rating 12 V / 9 Ah Battery type Sealed, lead-acid Extended battery capability Yes Electrical output
Receptacle Hardwired Topology Online/Double-conversion Wattage 3000 W VA rating 3000 VA Output waveform Sine wave Voltage 230V Output power factor 1 Output nominal voltage 230V default (200/208/220/230/240V) Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 3 Output frequency 50/60 Hz Feed type 1 Electrical input
Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240V) Input voltage range 176-276 V (100-276 V with derating) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Communications
Communication USB port (HID compliant)
Serial port (RS232)
Mini terminal block for remote On/Off
Mini-terminal block for remote power off
Mini-terminal block....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 3000i RT3U HotSwap HW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.