

INDUSTRIAL COMPONENT DATA

9PX6KIRTN-L 9104-LB12002 EATON ELECTRIC Eaton 9PX 6000i RT3U Netpack Li Ion

Brand: EATON - MOELLER | Manufacturer Part Number: 9PX6KIRTN-L



Manufacturer	EATON - MOELLER
MPN / Reference	9PX6KIRTN-L
Catalog number	9104-LB12002
Category	UPS
Minimum order	1 Pcs
Document ID	EO-53BBC776BE
Generated	2026-08-05

Product Overview

Eaton 9PX 6000i RT3U Netpack Li Ion

Eaton 9PX Lithium UPS Netpack, 6000 VA, 5400 W, Input: Hardwired, Outputs: (8) C13, (2) C19, Hardwired, Rack/tower, 3U, Network card included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX6KIRTN-L Model Code Eaton 9PX 6000i RT3U Netpack Li Ion UPC 786689772604 Product Length/Depth 685 mm Product Height 130 mm Product Width 440 mm Product Weight 35.8 kg Warranty 5 year Compliances CE Marked

TUV

cULus Listed

CSA 22.2 Certifications UL 1778

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Runtime graph Battery management Battery replacement Hot-swappable internal batteries and extended battery modules (EBMs) Battery quantity 15 Battery rating 6 Ah Battery type Lithium-ion Extended battery capability Yes Electrical output

Receptacle (8) C13, (2) C19, Hardwired Topology Online/Double-conversion Wattage 5400 W VA rating 6000 VA Output waveform Sine wave Voltage 230V Output power factor 0.9 Output nominal voltage 230V default (200/208/220/230/240V) Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 2 Output frequency 50/60 Hz Feed type 1 Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240V) Input voltage range 176-276 V (100-276 V with derating) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Communications

Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Dry contacts (4 outputs, relay, DB9)

DB15 for parallel operation

Network card

Expansion slots One slot, network card incl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 9PX6KIRTN-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.