

## INDUSTRIAL COMPONENT DATA

# A-PKZ0(230V50HZ)-PI 199339 Y7-199339 EATON ELECTRIC A-PKZ0(230V50HZ)-PI

Brand: EATON - MOELLER | Manufacturer Part Number: A-PKZ0(230V50HZ)-PI



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | EATON - MOELLER                           |
| MPN / Reference | A-PKZ0(230V50HZ)-PI                       |
| Catalog number  | Y7-199339                                 |
| Category        | Shunt release (for power circuit breaker) |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-7F4DF38019                             |
| Generated       | 2026-08-05                                |

## Product Overview

A-PKZ0(230V50HZ)-PI

Eaton Moeller® series A-PKZ0 Shunt release PKZ0(4), PKE, AC, 230 V 50 Hz, Push in terminals  
Shunt release with Push in terminals, for circuit-breaker PKZ(M)0 size

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Circuit Breakers PKZ

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series PKZ Shunt release Catalog Number 199339 Model Code A-PKZ0(230V50HZ)-PI  
EAN 4015081974238 Product Length/Depth 68 mm Product Height 91 mm Product Width 24 mm Product Weight 0.132 kg  
Compliances CE Marked

## RoHS conform Features &amp; Functions

Electric connection type Spring clamp connection

Push in terminals General

Suitable for Motor safety switch Used with Motor protective circuit-breaker Voltage type AC Climatic environmental  
conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating

Operational voltage 0.7- 1.1 x Us (DC)

0.7- 1.1 x Us (alternating voltage)

0.7 - 1.1 x Us (AC) Rated operational voltage (Ue) at AC - min 42 V Rated operational voltage (Ue) at AC - max 480 V  
Rated operational voltage (Ue) at DC - min 24 V Rated operational voltage (Ue) at DC - max 250 V Magnet system

Operational voltage 0.7- 1.1 x Us (DC)

0.7- 1.1 x Us (alternating voltage)

0.7 - 1.1 x Us (AC) Rated control supply voltage (Us) at AC, 50 Hz - min 230 V Rated control supply voltage (Us) at AC, 50  
Hz - max 230 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz -

max 0 V Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Nu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / A-PKZ0(230V50HZ)-PI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.