

INDUSTRIAL COMPONENT DATA

A-PKZ0(24VDC)-PI 199336 Y7-199336 EATON ELECTRIC

A-PKZ0(24VDC)-PI

Brand: EATON - MOELLER | Manufacturer Part Number: A-PKZ0(24VDC)-PI



Manufacturer	EATON - MOELLER
MPN / Reference	A-PKZ0(24VDC)-PI
Catalog number	Y7-199336
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-CEA847434C
Generated	2026-08-05

Product Overview

A-PKZ0(24VDC)-PI

Eaton Moeller® series A-PKZ0 Shunt release PKZ0(4), PKE, DC, 24 V DC, Push in terminals
Shunt release with Push in terminals, for circuit-breaker PKZ(M)0 size

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ Shunt release Catalog Number 199336 Model Code A-PKZ0(24VDC)-PI EAN 4015081974207 Product Length/Depth 68 mm Product Height 91 mm Product Width 24 mm Product Weight 0.128 kg
Compliances RoHS conform

CE Marked Features & Functions

Electric connection type Push in terminals

Spring clamp connection General

Suitable for Motor safety switch Used with Motor protective circuit-breaker Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating

Operational voltage Short-time operation 5 s

0.7 - 1.1 x Us (AC)

0.7- 1.1 x U_s (DC) Rated operational voltage (U_e) at AC - min 42 V Rated operational voltage (U_e) at AC - max 480 V
Rated operational voltage (U_e) at DC - min 24 V Rated operational voltage (U_e) at DC - max 250 V Magnet system
Operational voltage Short-time operation 5 s

0.7 - 1.1 x U_s (AC)

0.7- 1.1 x U_s (DC) Rated control supply voltage (U_s) at AC, 50 Hz - min 0 V Rated control supply voltage (U_s) at AC, 50 Hz
- max 0 V Rated control supply voltage (U_s) at AC, 60 Hz - min 0 V Rated control supply voltage (U_s) at AC, 60 Hz - max 0
V Rated control supply voltage (U_s) at DC - min 24 V Rated control supply voltage (U_s) at DC - max 24 V Contacts
Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts
(normally....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / A-PKZ0(24VDC)-PI with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.