

INDUSTRIAL COMPONENT DATA

MFD-AC-CP8-NT 274092 0004519711 EATON ELECTRIC

MFD-CPU, AC, with easy-NET

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-AC-CP8-NT



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-AC-CP8-NT
Catalog number	0004519711
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-F8C2B6FD97
Generated	2026-08-01

Product Overview

MFD-CPU, AC, with easy-NET

MFD-Titan Graphic Programmable Relay; 100-240 V AC; With EasyNet

Power supply module, Subrange: CPU modules, Degree of Protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4519711MFD-CPU, AC, with easy-NETPower supply module, Subrange: CPU modules, Degree of Protection: IP20Delivery program

Product rangeMulti-function-display MFD-TitanBasic functionPower supply unit/CPU modulesSubrangeCPU modulesSupply voltage100 - 240 V ACEasyNet/easyLinkmit easyNet

Descriptioncan be combined with display/operating unit MFD-80-.. and I/O module

Expandable: Digital/analog inputs/outputs and AS-Interface, PROFIBUS-DP, CANopen®, DeviceNet bus systems

Bussystem easyNet optional on board

Program and screen memory

Delivery with user program possible with MFD-COMBINATION product (Article no. 201801)DescriptionProgram and screen memory, with easyNetConnection typescrew terminalDegree of ProtectionIP20Technical data

GeneralStandardsEN 61000-6-1/-2/-3/-4, IEC 60068-2-6, IEC 60068-2-27Dimensions (W x H x D)107.5 x 90 x 30

mmWeight0.145 kgMountingFitted on the fixing shaft of the display or on top-hat rail according to IEC/EN 60715, 35 mm

deep (without display)Terminal capacitiesSolid0.2/4 (AWG 24 - 12) mm2Flexible with ferrule0.2/2.5 (AWG 24 - 12)

mm2Standard screwdriver3.5 x 0.6 mmClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °CCondensationTake appropriate measures to prevent condensationStorage- 40 - 70 °CRelative humidity, non-condensing (IEC/EN 60068-2-30)5 - 95 %Air pressure (operation)795 - 1080 hPaAmbient conditions, mechanicalProtection type (IEC/EN 60529, EN50178,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-AC-CP8-NT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.