

INDUSTRIAL COMPONENT DATA

AC16 AC16BS EATON ELECTRIC Fuse-link, low voltage, 16 A, AC 550 V, BS88, 21 x 114 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: AC16



Manufacturer	EATON - MOELLER
MPN / Reference	AC16
Catalog number	AC16BS
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-733C7FC58C
Generated	2026-08-06

Product Overview

16AMP 550Vac / 250Vdc INDUSTRIAL FUSE

Fuse-link, low voltage, 16 A, AC 550 V, BS88, 21 x 114 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 16 A, AC 550 V, BS88, 21 x 114 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-1, IEC 60269-1, Breaking Capacity 80 kA, Ceramic body

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number AC16 EAN 5027590491648 UPC 051712844741 Product Length/Depth 115 mm Product Height 90 mm Product Width 107 mm Product Weight 55.75 g

Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 16 A Voltage rating 550 Vac, 250 Vdc Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL

Product specifications

Fuse type AC Fitted with: Centre bolted tags Construction BS88

ETIM for AC16 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

550 V

Rated voltage DC (EF012281)

250 V

Rated current (EF000227)

16 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

2.9 W

Mounting holes (EF021553)

M6

Centre-to-centre distance of connections (EF021151)

97.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AC16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.